

RENGØRING AF ULTRA HH

1. Tag koppen af og tøm den for maling.
2. Rengør filter/låg og pakning.
3. Sæt en ny liner (pose) i koppen.
4. Fyld koppen med varmt vand og monter den igen.
5. **Vend sprøjten på hovedet** og drej returhansen til lodret position.
6. Tag aftræk og skyl sprøjten igennem. Trykregulatoren skal stå på 10.
7. Punkt 4 til 6 gentages minimum 3 - 4 gange, eller til vandet er rent.
8. Returhansen vendes til vandret position og en halv kop vand sprøjtes gennem dysen. (Vend dysen bagud for at mindske sprøjtetøv).
9. Sprøjt nu en smule Pump Armor igennem systemet. Dette er afgørende for sprøjtens levetid.



Returhane

OBS!

For at undgå beskadigelse af pumpen, skal al luft trykkes ud af posen, inden sprøjten bruges.



SE VIDEOEN

Vi har lavet en video om hvordan du rengør din Graco Ultra HH



PUMP ARMOR

Brug Pump Armor til rengøring og vedligeholdelse af din Ultra HH
Varenr.: GR253574

DYSEGUIDE

Materiale	Dyse	Filter	Trykregulator
Træ- og metalmaling	FFLP210 - FFLP410	Blå	3-4
Træbeskyttelse	FFLP412	Blå	3-4
Væg- og loftmaling	FFLP514	Sort	6-7

HOW TO CLEAN ULTRA HH

1. Remove the cup and empty it from paint.
2. Clean the filter, the lid and the gasket.
3. Put a new liner in the cup.
4. Fill the cup with hot water and put it back on the sprayer.
5. **Turn the sprayer upside down** and turn the prime valve to the vertical position.
6. Pull the trigger and rinse the sprayer. Set the pressure adjuster at level 10.
7. Repeat step 4 to 6 for a minimum of 3 - 4 times, or until the water is clean.
8. The prime valve is turned to a horizontal position and half a cup of water is sprayed through the tip. (Turn the tip backwards to reduce spray dust).
9. Spray Pump Armor through the system. This is crucial for the life of the sprayer.



Prime valve

ATTENTION!

To avoid damaging the pump, squeeze all air out of the liner before using the sprayer.



WATCH THE VIDEO

We have made this video, showing how to clean the Graco Ultra HH



PUMP ARMOR

Use Pump Armor to clean and maintain your Graco Ultra HH
Part no.: GR253574

TIP GUIDE

Material	Tip	Filter	Pressure adjuster
Paint for wood and metal	FFLP210 - FFLP410	Blue	3-4
Wood protection	FFLP412	Blue	3-4
Paint for wall and ceiling	FFLP514	Black	6-7